TECNOLOGIE CHIMICHE

TOVER S.R.L.

Via Rosa Luxembourg 2/A 10093 COLLEGNO (TO)

Tel.: +39-011/7792823 Fax.:+39-011/7792749 REG.IMP.TO

P.IVA 07783540011 R.E.A. N° 920259

e-mail: info@tover.com

Green Cleaner

ALIPHATIC ODORLESS THINNER WITH SLOW EVAPORATION

Aliphatic thinner with slow evaporation specific to dilute impregnation oil and wax based products or urethane-oil lacquers.

Green Cleaner is a blend of cicloaliphatic odorless hydrocarbons with excellent thinning and degreasing properties.

The product does not darken the wood.

Available in drums of 10 – 5 – 1 liters.



Application

TO DILUTE: as per quantities and percentages are concerned, follow the indications written in technical data sheets of the products to be diluted.

It will be important not to exceed the Voc content limit for products like Durolak OR Maxi and Durolak OR Maxi Color (see data on relative technical data sheets).

TO REMOVE OILS AND WAXES: in order to remove from the wood previous treatments made with oils or waxes or to remove excess of oil which does not dry, it is recommended to follow this procedure:

- spread Green Cleaner with a cloth or a roller on the surface to be treated
- remove the previous treatment with a monodisc with a green pad
- remove with a clean cloth all residues.

Then it is advised to finish with a impregnating product like oil or wax.

Notes

- ✓ Do not use Green Cleaner to dilute water-based or solvent-based products.
- ✓ Green Cleaner may be used like common white spirit and turpentine. It is anyway always better to check the compatibility with the product to be diluted.
- ✓ Green Cleaner can be used for clearing procedures of tools and machines used for the application of oils or oil-based lacquers.

Safety rules

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on the labels and consult safety data sheets before use.

Disposing of waste

Dispose unused product and empty containers according to the local law

