# LEGA STUCCO RS/20

**SOLVENT-BASED BINDER FOR MAKING FILLER**

Solvent-based film-forming resin to mix with sawdust to fill parquet gaps and fissures. Lega Stucco RS/20 dries quickly, it is easy sandable and it has got high filling properties.

I

## Technical data

| Chemical-Physical characteristics (20ºC - 60% R.H.) | | | |
|---|---|---|---|
| *Appearance* | Dense liquid | *Specific gravity* | 0,920 g/cm$^3$ |
| **Mixing ratios and Times (20°C - 60% R.H.)** | | | |
| *Mixing ratio* | Monocomponent | *Sanding* | 30' - 40' |
| *Dust dry* | 20' | ***Dilution*** | Diluente P/24 |
| **Technical characteristics** | | | |
| *Indicative coverage* | 10-20 sqm/lt | *Application temp.* | > 10 °C |
| **Storage and labeling** | | | |
| *Storage (original unopened packaging at amb. temp.)* | 12 months | *Symbols of danger* | F - Xi |
| ***Tools cleaning*** | Just after use clean with Solvente di Lavaggio S/23. | | |
| ***Packaging*** | Canisters of 5 and10 lt | | |

## Application

- Sand the wooden floor by coarse and medium grit size sandpaper to obtain a smooth surface, free from grease, oils and waxes.
- Collect sawdust from sanding and prepare a mixture with Lega Stucco RS/20 in the proper ratio (approximately 30%) to reach the thickness required: filler must be more or less thick referring to the size of fissures (thinner fissures => more liquid filler).
- Quickly and uniformly spread the filler on the floor using a stainless American spatula taking care to push into the gaps as much product as possible. If necessary repeat the operation.
- After drying (30-40 min) proceed to sand up to 100-120 grit size sandpaper. Before applying any coat carefully check that all the exceeding filler has been removed and clean the surface.

## Notes

- ✓ To obtain the same colour of the wood use the powder obtained from sanding operations.
- ✓ To fill wood holes or big fissures, use the specific two-component polyester filler Nodostuc.
- ✓ Overcoatable with solvent-based and water-based sealers and lacquers.

## Safety rules

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on the labels and consult safety data sheets before use.

## Disposing of waste

Dispose not used product and empty containers in accordance of local in force regulations.

TOVER S.R.L.
Via Rosa Luxembourg 2/A
10093 COLLEGNO (TO)
P.IVA 07783540011
R.E.A. n°920259
Tel.: +39-011/7792823
Fax: +39-011/7792749
www.tover.com
e-mail: info@tover.com
Made in Italy

Azienda Certificata
UNI EN ISO 9001:2008
Cert. N° 393

WARNING: The information reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated.
***REV.2 18-07-2013*** Current Technical Data Sheet replaces the previous one.