# 0 U

### TOVER S.R.L. Via Rosa Luxembourg 2/A 10093 COLLEGNO (TO) Tel.: +39-011/7792823 Fax.:+39-011/7792749 REG.IMP.TO P.IVA 07783540011 R.E.A. N° 920259

www.tover.com e-mail: info@tover.com

# RALLENTY

## ADDITIVE TO SLOW DOWN WATER-BASED VARNISHES DRYING TIME

RALLENTY is a specific additive which prolongs the open time of water-based varnishes if the room temperature is high and humidity level low. If added in the right proportion to varnishes, RALLENTY significantly slows down the drying time and limits the risk of overlapping and marks.

Generally speaking RALLENTY can be used to improve the levelling of any Tover water-based product.

### Physical characteristics (20°C - 60% R.H.) Transparent liquid Technical characteristics **Products** Any water-based primer Max. 5% or varnish from TOVER compatible Storage and Labelling Storage in original unopened NONE 24 months Symbol of risk

Packaging	Bottle of 0,5 l

# **Application**

Technical data

Before applying the water-based product, add a maximum of 5% of RALLENTY and mix it well. Then apply the varnish according to the normal indications of the specific technical data sheet.

# Notes

Aspect

Mixing ratio

packaging

Flash point

To add too much product does not improve its properties.

Non-flammable

RALLENTY is a product which helps finishing in non optimum conditions; it is recommended anyway to apply water-based systems in proper conditions of humidity and temperature (20°C, 65% R.H).

# Safety Rules

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on the labels and consult safety data sheets before use.

# Disposing of waste

Dispose unused product and empty containers according to the local law.

