

SIGIL CLACK

WATERBASED SEALANT FOR LAMINATES OR FLOATING T&G FLOORS

Single-component fluid sealant for treating the joints of floating floors, laminate or T&G type, also prefinished; ideal for elements suitable to be replaced.

Sigil Clack is particularly advised in case of damp environments like kitchens, bathrooms, because it creates a water-proof barrier avoiding the joints to expand. Sigil Clack is easy to apply thanks to the handy pouring lip on the bottle, it assures fast drying and very easy cleaning.



Technical data

| Physical characteristics (20°C – 60% R.H.) | | | |
|---|--|-------------------------|----------------------------|
| Appearance | White paste | Specific gravity | 1,05 g/cm ³ |
| Viscosity (Brookfield 25°C) | 10.000 mPa.s | | |
| Times (20°C – 60% R.H.) | | | |
| Open time | 5-10' | Light walking | 12-24 hours (See notes) |
| Time for setting | 1-2 hours | Complete hardening | 24-48 hours |
| Technical characteristics | | | |
| Yield | 50 linear mt with 500ml | Application temperature | > + 10°C |
| Elongation to break | > 200% (estimated value) | | |
| Storage and labeling | | | |
| Storage in original packing closed at T >+ 10°C | 12 months KEEP AWAY FROM FROST | Symbols of risk | NONE |
| Tools cleaning | When still fresh it can be cleaned just with water, when dry use acetone | | |
| Packaging | Bottles of 500 ml with pouring lip | | |

Application

Take care the surfaces to be treated are well clean and dry.

Cut the ending lip of the bottle with the needed section. Apply Sigil Clack on the male element and immediately proceed to coupling. Once the element is inserted make a weak pressure to improve a continuous seal. For remove exceeding product proceed as follow:

Cleaning after drying: when the sealant is dry remove it by finger or by suitable tool being careful not to scratch or damage the surface. Sigil Clack does not adhere to prefinished coats and it can be easily peeled out without using solvents.

Cleaning immediately: when the sealant is still fresh, take it away with a sponge or slightly damp cloth.

Cleaning after laying.

When it is possible to walk on the floor, clean the surface using the specific cleaner Ready-Pro removing halos and dirt.

Notes

- ✓ When dry, Sigil Clack becomes transparent.
- ✓ Even if the laid elements are set after few hours, we advise to wait at least for 12-24 hours before walking on. During this period the mechanical features grow up and local stress could affect the continuity of sealing
- ✓ In any case follow installation guidelines given by the floor manufacturer

Safety rules

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on labels and consult the safety data sheet before using the product.

Disposal of waste

Dispose unused product and empty packages according to local in force regulations.

WARNING: The information reported in present technical data sheet are for guidance only and they do not hold our responsibility; the environmental conditions and the employ modalities are out of our control. We advise to check that the product fits for the work to be done.

REV.5 30-03-2011. Current Technical Data Sheet replaces the previous one.



TOVER S.R.L.

Via Rosa Luxembourg 2/A
10093 COLLEGNO (TO)
P.IVA 07783540011
R.E.A. n°920259
Tel.: +39-011/7792823
Fax: +39-011/7792749
www.tover.com
e-mail: info@tover.com

