

# LVT Leveller

Ready-to-use grout smoother

Ready-to-use grout smoother to be applied before laying a bonded or floating LVT on pre-existing ceramic tiles. Easy to sand, it allows levelling up to 2 mm without creating thickness; sanding and laying are possible after just 2 hours. For indoor use only.

## Technical data at 20 °C – 60% R. H.

Appearance	White paste
Mix Ratio	Monocomponent
Density	about 1,8 kg/l
pH	7,5 - 8,0
Sanding	2 - 3 hours
Consumption	0,8 - 1,0 kg/m <sup>2</sup>
Application temperature	> 10 °C – Frost sensitive
Storage	12 months in original sealed packages at a temperature > 10 °C
Tool cleaning	Immediately after use with water
VOC	13 g/l
Packages available	5 – 15 kg buckets

### Application

The floors to be treated must be clean, dry and free of loose parts. Pay particular attention to cleaning the grouts. Apply the product with a metal spatula, taking care to completely fill the grouts without exceeding the thickness on the ceramic tiles. After drying, the product can be easily sanded and makes it possible to obtain a very smooth surface suitable for laying LVT, both floating and bonded. For bonding use products suitable for non-absorbent surfaces

### Notes

Do not use outdoor or in areas subject to continuous water stagnation.

Do not use in the presence of rising damp.

Frost sensitive.

### Safety rules

Product for professional use only. Strictly respect the information expressed on the label and consult the safety data sheet before using the product.

### Disposal

Dispose the unused product and empty packages in accordance with the local legislation in force.



Primers &  
Sub-floors

## LVT Leveller



### Certification



The advice in this technical data sheet is given for information only and does not in any way engage our responsibility, since the methods and conditions of use of the product are beyond our control. We advise you to check the actual suitability for the intended use.

Rev. 01 – 7/10/2019  
This technical data sheet replaces the previous ones.