

# Fondo Antitannino

## Isolating sealer for tannin

Water-based isolating sealer against tannin and stains to block the raising of colouring substances present into the wood. It enables a secure successive finishing with water-based coloured products, efficiently blocking stains due to tannin in woods like oak or chestnut or in exotic woods rich of colouring substances. The effect remains stable. It can be used with all our colouring water-based systems except with Belle Epoque stain. Fondo Antitannino slightly darkens the wood so the use is not recommended with transparent lacquers when a natural effect is requested.

## Technical data at 20 °C and 60% R.H

Aspect	Slightly yellow liquid
Density	1,023 kg/l
pH	5
Dust dry	15 – 20 minutes
Overcoating	3 – 4 hours
Dilution for spray application	10% with water
Consumption	10 – 12 m <sup>2</sup> /litre
Application temperature	> 10 °C – Frost sensitive
Storage	12 months in months in original closed packaging at temperature > 10 °C
VOC	14 g/litre
VOC limit (2004/42/CE)	Cat A/g (WB), limit 30 g/litre
Tools cleaning	Clean the roller just after using it with water and neutral soap through a "squeezeroller", till the roller is clean, if possible rinse with clean water. Keep the rollers into Soluzione S/28 duly diluted with water, rinse with clean water before using them.
Available packaging	5 litres drums, 1 litre bottles

## Application

Sand the wood floor to obtain a smooth surface without oil, grease, wax or previous lacquers traces.

Fill and smooth the surface using a water-based filler like Idrostucco RS/30 or solvent-based like Lega Stucco RS/A mixed with wood dust; complete the sanding cycle with a 150 – 180 grit abrasive paper.

Vacuum and clean the wood floor carefully before applying the primer. Always check that there are suitable conditions for lacquering.

Shake the drum and apply one coat of Fondo Antitannino by roller, brush or spray.

Once dry (3-4 hours) apply a first coat of colouring product following the instructions on technical data sheets. Do not sand the sealer to avoid reducing isolating properties.

## Notes

Do not mix Fondo Antitannino with other water-based primers or lacquers as not compatible.

Always wait the perfect drying of Fondo Antitannino before applying the finishing products. Do not use Fondo Antitannino over old lacquers or oils but only on perfectly sanded or raw woods.

Do not use Fondo Antitannino before our Belle Epoque stain.

Do not use Fondo Antitannino before an oil or solvent-based finish.



Varnishes &  
Finishing

## Fondo Antitannino



## Certifications



Tover S.r.l.  
Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY  
P. IVA 07783540011 - REA n. 920259  
Tel. +39/011.7792823 - Fax.+39/011.7792749  
[www.tover.com](http://www.tover.com) - [info@tover.com](mailto:info@tover.com)

Fondo Antitannino slightly darkens the wood so the use is not recommended with transparent lacquers when a natural effect is requested.  
Do not pour the finishing product directly on the floor.  
Use a proper container.  
Avoid direct sunrays on the floor during application.  
Avoid air flows.  
Switch the heating off, above all under heating.

### Safety norms

FOR PROFESSIONAL USE ONLY. Strictly respect the information reported on the label and consult the safety data sheet before using the product.

### Waste disposal

Dispose the not used product and empty containers in accordance with local in force regulations.



Varnishes &  
Finishing

## Fondo Antitannino



### Certifications



The information reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated. Rev 02 from 05-07-2019. Current Technical Data Sheet replaces the previous one



**Tover S.r.l.**  
Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY  
P. IVA 07783540011 - REA n. 920259  
Tel. +39/011.7792823 - Fax.+39/011.7792749  
[www.tover.com](http://www.tover.com) - [info@tover.com](mailto:info@tover.com)