

Pro Deck

Water-based impregnation product for outdoor wooden floorings

Water-based impregnation agent for the protection treatment of wooden floorings and other surfaces outside (decking, terraces, pools, furniture, etc.).

Pro-Deck deeply penetrates into the wood and preserves the surfaces from spots, UV rays, moss and lichens. It reduces humidity absorption leaving the wood breathe. It is easy to apply and refresh, it does not become yellow, does not crack. Pro-Deck exists in neutral (slightly amber) and coloured version.

Technical data at 20 °C - 60% r.h

Aspect	Coloured liquid
Density	0,95 – 0,98 kg/l
Viscosity	10" Ford cup n° 4
Gloss Level (60°)	5 – 7 gloss
Yield	10 – 12 m ² /litre
Application temperature	> 10 °C
Touch dry	15 – 20 minutes
Overcoating	3 – 4 ore
Indurimento completo	12 – 24 ore
Storage	12 mesi
VOC	< 25 g/l
VOC category	Cat A/e (WB), limit 130 g/litre
Tools cleaning	Clean the roller immediately after use with water and neutral soap till the water is transparent. Rinse with clean water. Store the rollers in diluted S/28 solution; rinse with water before use
Confezioni disponibili	1 litre, 2,5 litres, 10 litres

Use

New or fresh sanded wood

Thoroughly clean the dust and apply one or two coats of Pro Deck with a brush or roller. In the case of greasy and oily woods normally one coat is sufficient, in the other cases two are necessary. There is no need to sand between one hand and another.

Wood previously treated with oil

Wash the floor with undiluted Nettar 2 to remove all traces of old oil, then rinse thoroughly with water. If necessary, repeat the operation a second time. If grey areas are present, perform a Grey Free treatment followed by an abundant water wash. Once dry, apply one or two coats of Pro Deck as in the case of new wood.

Wood previously treated with Pro Deck

Wash the floor with diluted Deteroil (2 caps in 10 liters of water) and rinse with water. Any gray areas can be treated with Gray Free. After rinsing and drying, apply a coat of Pro Deck.

Maintenance

In order to clean a wooden floor treated with Pro-Deck, use Pulito Parquet or Deteroil detergents.



Varnishes & Finishing

Pro Deck



Certificazioni



Tover S.r.l.
Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax.+39/011.7792749
www.tover.com - info@tover.com

Notes

Stir before use to guarantee the colour

Before treating the whole surface, make some tests on a small area

Protect the treated floorings from rain for at least 12 hours in order to able a good drying.

The pigments absorb UV rays and slow down the natural wood deterioration

It is recommended to use the product at a temperature superior to +10°C

Safety Rules

Prodotto ad uso professionale. Rispettare rigorosamente quanto espresso in etichettatura e consultare la scheda dati di sicurezza prima dell'utilizzo del prodotto.

Disposing of waste

Dispose of the unused product and empty packages in accordance with the local legislation in force.



Varnishes &
Finishing

Pro Deck



Certificazioni



The information reported in present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated. Rev 02 – 03-10-2017. This technical data sheet replaces all the previous one.

TOVER[®]



Tover S.r.l.

Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax.+39/011.7792749
www.tover.com - info@tover.com