

# Tovcol Tackifast

Pressure sensitive acrylic adhesive. - Tackifier

Water based acrylic adhesive providing a permanently tacky film to lay and remove or replace carpets and LVT tiles without applying further adhesive or damaging tiles. Suitable for any tile backing on any sub-floor including under heating. Only for indoor.

## Technical data at 20 °C, 60% R.H.

Aspect	White viscous liquid
Density	1,00 kg/l
Waiting time	2 – 12 hours according to sub-floor and ambient conditions
Light traffic	Immediate
Ready for use	Immediate
Yield	100 – 200 g/m <sup>2</sup>
Application temperature	min + 10 °C, max + 35 °C
Storage	12 months in original packing. Protect from freeze
Tools Cleaning	With water till the product is fresh, with Solvente S23 if cured
Packing	15 kg pails

## Sub-floor preparation

Tovcol Tackifast can be applied on any sub-floor in good conditions i.e. even, strong, clean, without grease or other residues. The maximum acceptable humidity level is < 2,5% (2,2 % in case of under heating). On gypsum or anhydrite sub-floors the humidity must be less than 0,5% (0,3% in case of under heating). On dusty sub-floors apply a coat of Nano-Fix water-based primer. Under heating must be prepared according to the supplier instructions. Switch off heating 24 hours before laying.

## Application

Acclimate both the adhesive and the flooring at least 24 hours before laying. Accurately mix the adhesive before using it. Apply Tovcol Tackifast with a roller or a notched trowel (TBK A1), wait till the adhesive becomes transparent, from 2 to 12 hours according to ambient conditions, lay the carpet or LVT tiles or stripes within the adhesive open time. Periodically check the good transfer of the adhesive on the flooring back. Roll up the flooring with a 60 kg roller from the centre to the edges of the room in order to avoid air bubbles. Repeat the operation after 20-30 minutes. Immediately clean adhesive residues or spots with a wet cloth. Follow the flooring supplier instructions too.

## Notes

Do not use for floorings subject to constant water.  
Protect from freeze. Store at temperature superior to +5 °C.

## Safety rules

For professional use only. Strictly respect the information reported on the labels and consult the safety data sheet before using the product.

## Waste disposal

Dispose not used products and empty containers in accordance to local in force regulations.



Adhesives &  
Sealants

## Tovcol Tackifast



## Certifications



Tover S.r.l.  
Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY  
P. IVA 07783540011 - REA n. 920259  
Tel. +39/011.7792823 - Fax.+39/011.7792749  
[www.tover.com](http://www.tover.com) - [info@tover.com](mailto:info@tover.com)

The information reported in the present technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated. Rev 01 from 15-03-2019 Current Technical Data Sheet replaces the previous one.