

Antique

Water-based ageing stain for wood

Water-based reacting stain for wood. Antique reacts with the colouring substances present in the wood, including tannin and gives the surface an antique aged look, which can be further enhanced with a subsequent oil treatment. It can also be overcoated with two-component water-based lacquers. Particularly effective on tannin-rich woods.

Technical data at 20 °C and 60% r.h.

Appearance	Transparent liquid
Density	1.0 kg/litre
pH	11
Complete drying	12 hours
Possible dilution	With water, in any ratio
Yield	5 – 10 m ² /litre
Application temperature	> 10 °C
Storage	12 months in sealed packages and temperature > 10 °C
VOC	0 g/litre
Cleaning of tools	With water
Packaging available	1 litre bottles, 5 litres plastic cans

Instructions for use

The wood to be treated must be raw, free of any trace of previous oil, wax, lacquer or any treatments. Shake the product before use, apply a thick coat of Antique with a brush or roller and let it dry for at least 12 hours. We recommend to use brushes and rollers of synthetic material. The product can also be applied by dipping. To obtain lighter effects, the product can be diluted with water in any ratio. The product is corrosive, it is recommended to use protective gloves and goggles and to protect any delicate surfaces near the area to be treated. Once dry, the surface treated with Antique must be carefully brushed and vacuumed to eliminate the dust produced during the treatment, for this purpose a mechanical brushing machine or a buffing machine with green pad can be used. As a finishing treatment, we recommend using oil-based products such as L'Olio 100%, Crema d'Olio, Oil Pro or Maxi Oil in order to enhance the warm tone of the treatment with Antique. Alternatively, two-component water-based lacquers can be used.

Notes

Use gloves and protective glasses during use.

The final look of the wood depends on several factors, first of all the content of dyes in the wood, it is therefore important to always carry out preliminary ageing tests. Even different lots of the same wood can give different results. During these tests check the perfect adhesion of the finishes.

To evaluate the final color of the wood it is necessary to apply the complete cycle, Antique + finish.

In any case, avoid leaving stagnant products on the surface.

Always brush and vacuum the wood treated with Antique before applying the finish.

If you want to obtain a more intense ageing effect, use the Bosch Vej product.

Safety regulations

PRODUCT FOR PROFESSIONAL USE. Strictly comply with what is stated on the labeling and consult the safety data sheet before using the product. The use of suitable gloves and protective clothing is always recommended.

Disposal

Dispose of the unused product and empty packaging in accordance with the provisions of the local legislation in force.



Varnishes &
Finishing

Antique



The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 05 – 31/03/2020 This technical data sheet replaces the previous one.