

# Grey Free

Reviving agent for greying wood

Product for the treatment of greying wood subsequent to ageing and deterioration caused by atmospheric agents. Grey Free allows to remove the superficial grey patina by restoring the original colour of the wood.

Grey Free can be used on any wooden surface such as floors, balconies, shutters, coverings, etc. You can also apply it vertically without dripping.

After rinsing and drying, the wood can be treated with any finishing product.

## Technical data at 20 °C e 60% R.H.

Appearance	Transparent liquid
Density	1.00 kg/litre
pH	2
Drying time	4 – 8 hours depending on the environmental conditions and the absorption of the wood
Yield	About 5 m <sup>2</sup> / litre
Application temperature	> +10 °C
Storage	12 months in original sealed packages
Tool cleaning	With water
Packages available	0.5 litres with spray, 1 litre bottles, 5 litres cans

## Instructions for use

The wood to be treated must be free of residues from previous lacquering or any other treatment, coarse dirt and any wood fibers that no longer adhere. Carry out a thorough mechanical cleaning of the wood with a hard brush, a buffing machine or a pressure washer according to the type and extent of the surface to be treated. To remove traces of previous oil treatments, it is possible to wash with Nettare according to the instructions in the relative technical data sheet.

Apply Grey Free by spraying it on the surface until saturation and leave it to act for 10 – 15 minutes. Rinse thoroughly with water to remove dirt and product residues. Let it dry. If necessary, repeat the operation.

After the wood has completely dried, any type of protective impregnating or finishing treatment for outdoors is possible.

### Notes

It is advisable to always carry out a preliminary treatment test to check the final aesthetic appearance.

Grey Free is an acid product, avoid contact with metallic elements or concrete subfloors, in case it happens you take care to immediately rinse thoroughly.

In the presence of wood with rotted areas, try to identify if it exists and it is possible to eliminate the cause that caused this phenomenon.

## Safety regulations

PRODUCT FOR PROFESSIONAL USE. Strictly comply with what is stated on the labeling and consult the safety data sheet before using the product. Wear gloves and protective clothing during application and ventilate the environment well if applied indoors.

## Disposal

Dispose of the unused product and empty packaging in accordance with the provisions of the local legislation in force..



Cleaning & Maintenance

## Grey Free



## Certifications



The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 03 – 27/02/2020 This technical data sheet replaces the previous one