

Lega Stucco RS/20

Solvent-based filler for wood floors

Fast drying solvent-based filler, to be mixed with wood powder for grouting and smoothing parquet before lacquering. To obtain a colour of the filling as similar as possible to that of the wood, we recommend using the same powder got by sanding the wood floor to be treated. It can be overcoated with all Tover primers and lacquers, both solvent and water-based.

Technical data at 20 °C e 60% r.h.

Appearance	Transparent viscous liquid
Density	0.921 kg/litre
Dust dry	20 minutes
Ready for sanding	After 30 – 40 minutes
Possible dilution	Diluente P24
Yield	10 – 20 m ² /litre
Application temperature	From +10 to +35 °C
Tools cleaning	Immediately after use with Solvente di Lavaggio S23
Storage	12 months in original sealed packaging
Packaging	5 and 10 liter plastic cans

Instructions for use

Sand the wood floor with a coarse and then medium grid abrasive paper to get a smooth surface free of previous lacquers, oils, greases and waxes. Collect the wood dust of the second sanding and mix it with the Lega Stucco RS/20 to obtain a dough of the desired consistency (mix ratio up to 30% of wood dust).

Spread quickly and evenly on the floor with an American spatula, taking care to make it penetrate at best into the cracks. If necessary, repeat the operation.

Wait for the complete drying and then finish the preparation of the floor using a 100 – 120 grit abrasive. Before proceeding with the finishing cycle, make sure to remove all excess grout.

Safety regulations

PRODUCT FOR PROFESSIONAL USE: Strictly comply with what is stated on the labelling and consult the safety data sheet before using the product.

Disposal

Dispose of the unused product and empty packaging in accordance with the provisions of the local legislation in force.



Varnishes &
Finishing

Lega Stucco RS/20



Certifications



Tover S.r.l.
Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax.+39/011.7792749
www.tover.com - info@tover.com

The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 03 – 24/03/2020 This technical data sheet replaces the previous one.