

Tovcol SR

Two-component polyurethane adhesive for small repairs

Tovcol SR is a two-component polyurethane adhesive with very fast setting, for quick bonding and repairs of parquet on any type of substrate, it allows the execution of any sanding in a very short time. Free of water and solvents. It can be used to fix quickly the first wooden pieces in particular installations such as herringbones

Technical data – 20 °C, 60% H.R.

Aspect	Comp. A – Thick oak-coloured paste Comp. B – Dark liquid
Mixing ratio	9 : 1 by weight
Mixture density	1,650 kg/litre
Pot-life	10 – 12 minutes
Time before sanding	1 hour and 30'
Complete curing	3 days
Shear strength according to EN 14293	> 3 N/mm ²
Application temperature	From + 10 to + 35 °C
Stockage	12 months in sealed packages – Frost sensitive
Tool cleaning	Immediately after use with Solvente di Lavaggio S23
Packaging	0,9 + 0,1 kg pot

Method of use

Make sure that the subfloor is clean and ready for wood floor installation, if necessary use a suitable primer, we recommend Primer PU100 for its hardening speed property.

Tovcol SR is a very quick adhesive, therefore prepare in advance the wood pieces to be installed.

Prepare the mixture by pouring component B into the container of component A, mix thoroughly until complete homogenization. We always recommend mixing the complete package, errors in the employment relationship can lead to various drawbacks such as poor mechanical properties and lacquering defects in correspondence of the joints between the boards.

During installation, avoid wetting the side of the wood plank with adhesive, this incorrect practice prevents the natural dimensional movements of the wood and can cause over time big anomalous or in extreme cases even breakage of the wood.

Cleaning of pre-lacquered surfaces from residues of Tovcol SR must be carried out with still fresh adhesive using the Stripcoll cleaner. Once hardened, the adhesive is hard to remove and you can do it only mechanically.

Notes

Frost sensitive

Always mix the whole package.

Do not use outdoors.

Safety regulations

PROFESSIONAL USE PRODUCT. Strictly comply with what is stated on the label and consult the safety data sheet before using the product.

Disposal

Dispose of the unused product and empty packaging in accordance with the provisions of the local legislation in force.



Adhesives
& Sealants

Tovcol SR



Certifications



The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the actual suitability for the intended use.

Rev 06 – 01/10/2020 This technical data sheet cancels and replaces the previous one.