# Adesol 100

#### Expansion adhesive for repairs

Solvent-free single-component polyurethane adhesive with expansive action, suitable for quick fixing and repairs of wooden elements not perfectly bonded to the subfloor. Adesol 100 can be used both before and after sanding your wood floor.

### Dati tecnici 20 °C e 60% u.r.

Appearance	Viscous brown liquid
Density	1.150 kg/litre
Walkability	6 – 8 hours
Sanding	24 hours
Application temperature	From + 5 to +35 °C
Tool cleaning	Immediately after use with Solvente di Lavaggio S/23. If Adesol 100 has hardened, it can only be removed mechanically.
Storage	12 months in original sealed packaging – Frost sensitive.
Packaging	500 ml bottles



## Adesol 100



#### Modalità d'uso

**For repairs before lacquering**: drill a 4 mm hole and inject the product, preceded by a few drops of water to accelerate the expansion and hardening reaction. Place a weight on the affected planks to avoid excessive swelling. After hardening, sand and fill the affected part before proceeding with finishing.

**Repairs on already lacquered wood floor**: spread some paste wax, for example Universal Wax, in the affected area to avoid damaging the lacquer during the repair, let the wax dry for a few hours then proceed as in the previous case. In this case, it is very important to place an adequate weight on the planks concerned to avoid swelling that would be hard to repair later.

After hardening, remove the leaked product, remove the wax and grout the hole with hot solid wax or with Full Gap colored acrylic sealant.

#### Safety rules

PRODUCT FOR PROFESSIONAL USE. Strictly comply with the labeling and consult the safety data sheet before using the product.

#### Disposal

Dispose of unused product and empty packs in accordance with local legislation.

#### Certifications





The information contained in this technical data sheet are for guidance only and they do not hold our responsibility. Adapt the use of our products to the environmental conditions and materials to be treated. Rev 05 – 23/03/2020 Current Technical Data Sheet replaces the previous one.







Tover S.r.l. Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY P. IVA 07783540011 - REA n. 920259 Tel. +39/011.7792823 - Fax.+39/011.7792749 www.tover.com - info@tover.com