# Rinovoil

#### Maintenance oil

Rinovoil is a ready-to-use blend of oils and hard waxes for the extraordinary maintenance of floors and other oil-treated wooden surfaces. It is recommended for restoring oil-treated floors when they are worn and dull. Also suitable for outdoor. Available in neutral and white versions.

#### Technical data at 20 °C – 60% r.h.

Aspect	Amber or white liquid
Density	0,820 kg/litre
Spreading time	15 – 20 minutes
Dry to touch	6 hours
Walkability	12 hours
Possible polishing	24 hours
Application temperature	From + 15 to + 35 °C
Yeld	About 80 m²/litre
Tools cleaning	Diluente RMD 91 or Greencleaner
Storage	At least 12 months in original sealed packaging stored at room temperature.
Packaging	1 litre cans

#### **Application**

Remove dust and impurities with a broom or vacuum cleaner. Wash with Deteroil to remove dirt and any greasy substances present on the surface. Let it dry. Mix the product thoroughly before application. Spread Rinovoil homogeneously with a clean cloth soaked in the product. Within 15-20 minutes distribute the product and remove any excess using a floor machine with a green pad. If necessary, after 12 hours, a second coat of product can be applied in the same way.

#### **Notes**

Avoid washing the surfaces for the first 15-20 days after applying Rinovoil.

Do not use on varnished wood.

Always apply the recommended quantities, do not exceed, an excess of product can lead to weak and sticky finish.

High humidity, low temperatures and very resinous woods can slow down the drying of Rinovoil.

### Safety rules

PRODUCT FOR PROFESSIONAL USE. Strictly comply with the labelling and consult the safety data sheet before using the product.

Attention! Rags, cloths and sponges soaked in the product can ignite by selfignition: Wet them abundantly with water, let them dry and dispose of them in compliance with current legislation.

#### Disposal

Dispose of unused product and empty packages in accordance with local legislation.







## Rinovoil



Certifications

The advice in this technical bulletin is given for information only and does not engage our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend verifying the actual suitability for the intended use.

Rev 04 – 08/11/2021. This sheet cancels and replaces the previous