

Primer C1

Water based primer

One-component acrylic water-based primer that guarantee optimal penetration even in poorly absorbent substrates. Suitable as an anti-dust primer and surface consolidator on absorbent substrates based on cement, gypsum, anhydrite and similar. Suitable for underfloor heating. Prevents excessive water absorption when bonding resilient floors with adhesives based on acrylic dispersions. Not suitable for bonding with two-component or silane adhesives. Not suitable for parquet.

Technical data at 20 °C – 60% r.h.

Appearance	Green liquid
Density	1,011 kg/litre
Walkability	1 hour
Waiting time for installation	2 hours
Possible dilution	Water
Yield	5 – 10 m ² /litre
VOC	< 0,1 g/litre, cat A/h (WB), limit 50 g/litre (2004/42/CE)
Application temperature	From +10 to +35 °C
Storage	12 months in original sealed packaging - Protect from freezing
Tools cleaning	Immediately after use with water
Packaging	5 and 10 liter cans

Application

The substrate to be treated must be clean, dry, free from grease, oil, paint and any other substance that could prevent the product from penetrating. Any residues must be removed before applying the primer. Apply Primer C1 with a roller or brush, favoring its absorption. Do not exceed the quantity of product to avoid the formation of a superficial film which must then be removed. After drying (about 2 hours) proceed with laying the floor.

Notes

Protect from frost.

Use Primer C1 only on absorbent surfaces.

In the case of low porosity substrates, it is possible to dilute Primer C1 up to 50% with water.

Do not use Primer C1 on wet surfaces or surfaces subject to possible rising damp.

Do not use Primer C1 before gluing with two-component or silane adhesives, in these cases use Nanofix.

Do not use Primer C1 before gluing wooden floors, use Nanofix instead.

Safety rules

PRODUCT FOR PROFESSIONAL USE. Strictly respect what is stated in the labeling and consult the safety data sheets before using the product.

Disposal

Dispose of unused product and empty packages in accordance with local legislation.



Primers & subfloors

Primer C1



Certifications



The advice in this technical bulletin is given for information only and does not engage our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend verifying the actual suitability for the intended use.

Rev 03 – 16/11/2021. This sheet cancels and replaces the previous one.



Tover S.r.l.
Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax. +39/011.7792749
www.tover.com - info@tover.com