

Fondo Isolante AL

Alcohol-based impregnating sealer

Fast-drying solvent-based primer. Easy to apply, it guarantees a good coverage and excellent insulating properties. It can be overcoated with any Tover lacquer, both water-based and solvent-based, excluding oil-based products.

Technical data at 20 °C and 60% R.H

Appearance	Transparent liquid
Density	0,820 kg/litre
Dust free	5 – 10 minutes
Overcoatable	1 – 2 hours
Ready for sanding	1 – 2 hours
Yield	10 – 12 m ² /litre
Application temperature	From + 10 to + 35 °C
VOC	700 g/liter, cat A/f (SB), limit 700 g/litre (2004/42/EC)
Tools cleaning	Solvente di Lavaggio S/23
Storage	12 months in original sealed packaging
Available packaging	5 and 10 liter plastic cans

Instructions for use

Sand the wood floor in order to obtain a surface free of oils, greases, waxes, lacquers or any previous treatment. Fill and level the surface using a water-based filler such as Idrostucco RS/30 or solvent-based fillers such as Lega Stucco RS/A or Lega Stucco RS/20; complete the sanding cycle with a 150 – 180 grit.

Vacuum and carefully clean the wood floor before applying the sealer. Always check that there are suitable conditions for lacquering. Shake the plastic can well and apply Fondo Isolante AL with a roller or a brush. After drying, apply the chosen finishing, which can be either a solvent or a water-base. Avoid sanding if possible, especially in the case of water-based finishes. If sanding is absolutely necessary, we recommend to apply another coat of Fondo Isolante AL before the finishing.

Safety regulations

PRODUCT FOR PROFESSIONAL USE. Strictly respect what is stated on the label and consult the safety data sheet before using the product.

Disposal

Dispose of the unused product and empty packaging in accordance with the provisions of current legislation.



Varnishes & Finishing

Fondo Isolante AL



The recommendations in this technical data sheet are given for information only and do not bind our responsibility in any way since the methods and conditions of use of the product are beyond our control. We recommend checking the suitability for the intended use.

Rev 02 – 2 /03/2020 – This technical data sheet replaces the previous one.

TOVER[®]



Tover S.r.l.

Via Rosa Luxemburg, 2/A - Collegno (TO) - ITALY
P. IVA 07783540011 - REA n. 920259
Tel. +39/011.7792823 - Fax. +39/011.7792749
www.tover.com - info@tover.com